

3  
JAHRE GARANTIE



weiß



grau



schwarz



Artikel	Watt (W)	Lichtfarbe	Lumen (LM)	CRI	Abstrahlwinkel	Input Voltage (V)	IP Schutzart	Ø x H	Gehäuse (Abschlussring)
DBW12W3	12	3000K	830	>80	120°	AC 220V-240V/50Hz	IP66	300 x 90	weiß
DBW12W4	12	4000K	830	>80	120°	AC 220V-240V/50Hz	IP66	300 x 90	weiß
DBB12W3	12	3000K	830	>80	120°	AC 220V-240V/50Hz	IP66	300 x 90	schwarz
DBB12W4	12	4000K	830	>80	120°	AC 220V-240V/50Hz	IP66	300 x 90	schwarz
DBG12W3	12	3000K	830	>80	120°	AC 220V-240V/50Hz	IP66	300 x 90	grau
DBG12W4	12	4000K	830	>80	120°	AC 220V-240V/50Hz	IP66	300 x 90	grau

#### Eigenschaften:

- Gehäuse: PC
- Diffusor/Scheibe: PC (Polycarbonat)
- DB-Series sind ausgestattet mit Treiber und LED-Board
- Sehr stabile Leuchte: IK-10
- Für Wand- oder Deckenmontage (Innen- oder Außenbereich)
- Abdeckung opales UV-stabilisiertes Polycarbonat
- Mittlere Lebensdauer > 40.000h

#### Anwendungsbereiche:

Sanitärbereiche, Flure, aber auch in Außenbereichen.

#### Lichtverteilungskurve:

LVK DBW12W3

